

KOMPAKT outlet, Category 5E

- P/N: 501122 floor / duct-mounted
- P/N: 501122-UP flush-mounted
- P/N: 501122-AP wall-mounted

1
Gigabit

Cat.5E

100
MHz



features

- fast and easy installation using 110 or Krone® insertion tool
- LSA termination blocks
- enables transmission of all high-speed protocols including 1000BASE-T
- guarantees a bandwidth of 100 MHz
- perfectly shielded against electromagnetic interference
- angled entry
- wall-mounted outlets are suitable for duct and channel systems of other manufacturers such as Legrand, OBO Bettermann, Elektraplan Niedax, etc

mechanical properties

outlet		floor / duct-mounted	flush-mounted	wall-mounted
Dimensions	frame	-	80x80 mm	80x80 mm
	central module	50x50 mm	50x50 mm	50x50 mm
Color		white RAL9010	white RAL9010	white RAL9010
Surface		shiny	shiny	shiny
Required installation depth		35 mm	30 mm	-

related products

P/N: KE300S24	FTP (F/UTP) cable 4x2xAWG24, Category 5E, 125 MHz, shielded
P/N: KE300S24LSOH	FTP (F/UTP) cable 4x2xAWG24, Category 5E, 125 MHz LSOH, shielded
P/N: KE300S24OUT	FTP (F/UTP) cable 4x2xAWG24, Category 5E, 125 MHz for outdoor use, shielded
P/N: KEL-C5E-F-xxx	FTP patch cable, Category 5E, LSOH, shielded
P/N: KEN-C5E-T-xxx	S/FTP patch cable, Category 5E, shielded